

BackLess® Wall Textiles

Specifications

WEAVE	SIZE	WEIGHT (+/- 10%) OZ/Y ²	WEIGHT (+/- 10%) KG/M ²	THICKNESS (+/- 10%) INCHES	THICKNESS (+/- 10%) MM
Bamboo	72" (1.83 m)	15.60	0.529	0.048	1.22
Basketweave, FG-Core	72" (1.83 m)	26.00	0.882	0.052	1.32
Basketweave, P-Core	72" (1.83 m)	20.80	0.705	0.044	1.12
Bouclé	72" (1.83 m)	21.00	0.712	0.046	1.17
Dart	72" (1.83 m)	26.00	0.882	0.046	1.17
Frost	72" (1.83 m)	33.60	1.140	0.092	2.34
Ikat	72" (1.83 m)	23.20	0.787	0.048	1.22
Mini Basketweave	72" (1.83 m)	21.10	0.715	0.040	1.02
Mosaic	72" (1.83 m)	17.30	0.587	0.039	0.99
Plaid	72" (1.83 m)	17.70	0.600	0.039	0.99
Reed	72" (1.83 m)	19.70	0.668	0.056	1.14
Rib Weave	72" (1.83 m)	28.50	0.966	0.081	1.98
Shade	72" (1.83 m)	22.20	0.753	0.046	1.17
Speckle	72" (1.83 m)	23.20	0.787	0.052	1.32
Tidal	72" (1.83 m)	18.60	0.630	0.064	1.63
Twill	72" (1.83 m)	19.30	0.654	0.052	1.32
Wave	72" (1.83 m)	17.00	0.576	0.042	1.07

FLAMMABILITY
ASTM E84
ADHERED

FLAMMABILITY
ASTM E84
ADHERED

WALL TEXTILES
DURABILITY
ASTM F 793

CLASSIFICATION

Class A

Class A

Cat VI, Type III

Commercial

WINDOW COVERING
NFPA 701 METHOD 1

ABRASION
WYZENBEEK

Pass

100,000