

Wall Textiles

Specifications

| WEAVE | SIZE | WEIGHT (+/- 10%) OZ/Y ² | WEIGHT (+/- 10%) KG/M ² | THICKNESS (+/- 10%) INCHES | THICKNESS (+/- 10%) MM |
|----------------------|--------------|--|--|----------------------------------|------------------------------|
| Bamboo | 72" (1.83 m) | 20.06 | 0.584 | 0.059 | 1.50 |
| Basketweave, FG-Core | 72" (1.83 m) | 30.70 | 0.870 | 0.072 | 1.83 |
| Basketweave, P-Core | 72" (1.83 m) | 25.80 | 0.731 | 0.070 | 1.78 |
| Bouclé | 72" (1.83 m) | 25.80 | 0.731 | 0.071 | 1.80 |
| Dart | 72" (1.83 m) | 30.70 | 0.870 | 0.072 | 1.83 |
| Frost | 72" (1.83 m) | 38.40 | 1.089 | 0.104 | 2.64 |
| Glow | 70" (1.78 m) | 18.70 | 0.530 | 0.056 | 1.42 |
| Ikat | 72" (1.83 m) | 27.70 | 0.785 | 0.064 | 1.63 |
| Mini Basketweave | 72" (1.83 m) | 22.20 | 0.629 | 0.060 | 1.52 |
| Mosaic | 72" (1.83 m) | 12.20 | 0.629 | 0.063 | 1.60 |
| Plaid | 72" (1.83 m) | 22.20 | 0.629 | 0.061 | 1.55 |
| Reed | 72" (1.83 m) | 24.80 | 0.703 | 0.059 | 1.50 |
| Rib Weave | 72" (1.83 m) | 33.50 | 0.950 | 0.090 | 2.29 |
| Savile | 72" (1.83 m) | 25.80 | 0.731 | 0.071 | 1.80 |
| Shade | 72" (1.83 m) | 26.90 | 0.763 | 0.066 | 1.68 |
| Speckle | 72" (1.83 m) | 28.10 | 0.796 | 0.065 | 1.65 |
| Tidal | 72" (1.83 m) | 23.20 | 0.656 | 0.101 | 2.57 |
| Twill | 72" (1.83 m) | 24.20 | 0.686 | 0.063 | 1.60 |
| Wabi Sabi | 72" (1.83 m) | 31.30 | 0.882 | 0.098 | 2.49 |
| Wave | 72" (1.83 m) | 22.20 | 0.629 | 0.060 | 1.52 |

FLAMMABILITY ASTM E84 ADHERED

Class A
Class A

FLAMMABILITY ASTM E84 ADHERED

Class A
Class A

WALL TEXTILES DURABILITY ASTM F 793

Cat VI, Type III
Glow, Bamboo; Cat V, Type II

CLASSIFICATION

Commercial
Commercial

WINDOW COVERING NFPA 701 METHOD 1

Pass

ABRASION WYZENBEEK

100,000