

Custom Rugs

US Testing

WEAVE	WIDTH	WEIGHT (+/- 10%) LBS/SF	THICKNESS (+/- 10%) INCHES
Arrow	72", or max 18' with seams	0.33	0.13
Bamboo	72", or max 18' with seams	0.30	0.15
Basketweave, FG-Core	72", or max 18' with seams	0.37	0.15
Basketweave, P-Core	72", or max 18' with seams	0.33	0.14
Bouclé	72", or max 18' with seams	0.32	0.15
Cane	72", or max 18' with seams	0.34	0.14
Chime	72", or max 18' with seams	0.34	0.13
Chord	72", or max 18' with seams	0.31	0.14
Dart	72", or max 18' with seams	0.37	0.15
Flare	72", or max 18' with seams	0.35	0.14
Fresco	72", or max 18' with seams	0.34	0.14
Heddle	72", or max 8' with seams	0.41	0.16
Ikat	72", or max 18' with seams	0.35	0.15
Mini Basketweave	72", or max 18' with seams	0.33	0.14
Mosaic	72", or max 18' with seams	0.31	0.14
Overshot	72", or max 18' with seams	0.35	0.14
Plaid	72", or max 18' with seams	0.31	0.14
Reed	72", or max 18' with seams	0.33	0.16
Rib Weave	72", or max 18' with seams	0.39	0.18
Savile	72", or max 18' with seams	0.32	0.15
Shade	72", or max 18' with seams	0.34	0.15
Shuttle	72", or max 18' with seams	0.35	0.13
Speckle	72", or max 18' with seams	0.35	0.13
Wave	72", or max 18' with seams	0.31	0.14
Woodgrain	72", or max 18' with seams	0.31	0.13

TEST CONDUCTED	TEST NAME	RESULT
Critical Radiant Flux	ASTM E648	Class 1
Compression Recovery after 96 hours	Static Load	< 94%
Surface Flammability/Methamime Pill Test	CSPC FF 1-70/ASTM D2859	Pass

JANUARY 30, 2024

CHILEWICH 39 WEST 19TH STREET, NEW YORK 10011
 TEL 212 679 9204 FAX 212 679 9205 CHILEWICHAD.COM
 ©2024 CHILEWICH | SULTAN LLC. ALL RIGHTS RESERVED.

chilewich®