

Wall Textiles

Specifications

WEAVE	SIZE	WEIGHT (+/- 10%) LBS/SF	WEIGHT (+/- 10%) KG/M ²	THICKNESS (+/- 10%) INCHES	THICKNESS (+/- 10%) MM
Arrow	72" (1.83 m)	0.19	0.91	0.06	1.57
Bamboo	72" (1.83 m)	0.15	0.71	0.06	1.50
Basketweave, FG-Core	72" (1.83 m)	0.21	1.04	0.07	1.83
Basketweave, P-Core	72" (1.83 m)	0.18	0.87	0.07	1.78
Bouclé	72" (1.83 m)	0.17	0.81	0.07	1.80
Cane	72" (1.83 m)	0.19	0.94	0.07	1.80
Chime	72" (1.83 m)	0.19	0.94	0.07	1.75
Chord	72" (1.83 m)	0.16	0.80	0.07	1.88
Dart	72" (1.83 m)	0.21	1.04	0.07	1.83
Flare	72" (1.83 m)	0.18	0.86	0.07	1.80
Fresco	72" (1.83 m)	0.19	0.91	0.08	1.96
Ikat	72" (1.83 m)	0.19	0.94	0.06	1.63
Mini Basketweave	72" (1.83 m)	0.18	0.86	0.06	1.52
Mosaic	72" (1.83 m)	0.16	0.76	0.06	1.60
Overshot	72" (1.83 m)	0.19	0.94	0.07	1.75
Plaid	72" (1.83 m)	0.16	0.76	0.06	1.55
Reed	72" (1.83 m)	0.17	0.84	0.06	1.50
Rib Weave	72" (1.83 m)	0.23	1.14	0.09	2.29
Savile	72" (1.83 m)	0.17	0.81	0.07	1.80
Shade	72" (1.83 m)	0.19	0.91	0.07	1.68
Shuttle	72" (1.83 m)	0.19	0.94	0.08	1.91
Speckle	72" (1.83 m)	0.20	0.95	0.07	1.65
Wave	72" (1.83 m)	0.15	0.75	0.06	1.52
Woodgrain	72" (1.83 m)	0.16	0.76	0.06	1.60

FLAMMABILITY
ASTM E84
ADHERED

WALL TEXTILES
DURABILITY
ASTM F793

CLASSIFICATION

Class A

Cat VI, Type III
Bamboo; Cat V, Type II

Commercial