

Custom Floor Mats

EU Testing

WEAVE	SIZE	MASS EN 430 KG/M ²	THICKNESS (+/- 10%) MM
Bamboo	1.83 m, or wider with seams	1.40	3.76
Basketweave, FG-Core	1.83 m, or wider with seams	1.75	3.86
Basketweave, P-Core	1.83 m, or wider with seams	1.57	3.66
Bouclé	1.83 m, or wider with seams	1.28	3.71
Dart	1.83 m, or wider with seams	1.75	3.86
Frost	1.83 m, or wider with seams	2.00	4.88
Heddle	1.83 m, or wider with seams	1.66	4.57
Ikat	1.83 m, or wider with seams	1.65	3.76
Mini Basketweave	1.83 m, or wider with seams	1.58	3.56
Mixed Weave	1.83 m, or wider with seams	1.48	3.72
Mosaic	1.83 m, or wider with seams	1.45	3.54
Plaid	1.83 m, or wider with seams	1.65	3.76
Reed	1.83 m, or wider with seams	1.53	3.96
Rib Weave	1.83 m, or wider with seams	1.83	4.60
Savile	1.83 m, or wider with seams	1.36	3.30
Scout	1.83 m, or wider with seams	1.23	3.56
Shade	1.83 m, or wider with seams	1.62	3.71
Speckle	1.83 m, or wider with seams	1.65	3.91
Wave	1.83 m, or wider with seams	1.44	3.61

TEST CONDUCTED	TEST NAME	RESULT
Critical Radiant Flux	ASTM E648	Class 1
Compression Recovery after 96 hours	Static Load	<94%